



## REVPURE GL-4 80W-90

### PRODUCT DESCRIPTION:

RevPure GL-4 80W-90 is a high-performance, high-pressure gear oil blended from selected base oils and multifunctional additives. This oil is suitable for a wide range of drives and transmissions. A high load-carrying capacity guarantees optimum gearbox lubrication even at high temperatures.

### APPLICATION:

For transmissions and final drives with normal to high loading.

### FEATURES & BENEFITS:

- Excellent resistance to aging.
- High-pressure absorption capability.
- Reduces transmission noise.
- Excellent viscosity/temperature properties.
- Does not attack common sealing materials.

### PERFORMANCE LEVELS: Meets or Exceeds:

- API GL-4
- MIL-L 2105

### TYPICAL PROPERTIES:

PARAMETERS	ASIM	UNIT	REVPURE GL-4
Grade			<b>80W-90</b>
Kinematic Viscosity @ 104°F / 40°C	D-7042	cSt	TBR
Kinematic Viscosity @ 212°F / 100°C	D-7042	cSt	14.8
Viscosity Index	D-2270	-	145
Density@15°C/ 60°F	D-4052	g/cm <sup>3</sup>	TBR
Flash Point (min)	D-92	°C	220
Pour Point (max)	D-97	°C	-27
Brookfield Viscosity @-26	D-2983	mPas	<150,000

**DISCLAIMER:** The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.