



## VELOCITY NANO XP

### PRODUCT DESCRIPTION:

Velocity Nano XP oils are formulated with high performance base stocks and fortified with proprietary advanced additive system, designed to provide our longest lasting engine protection. These oils control oil breakdown to maximize wear protection and prevent harmful sludge during extended oil change intervals. Velocity Nano XP oils are designed to provide protection against LSPI (low speed pre-ignition) in TGDl engines and to help limit turbo coking and deposits that can lead to turbo charger temperature increase or bearing failure.

### APPLICATION:

Recommended for North American, European & Japanese high output gasoline engines in passenger cars, sport utility vehicles, vans, and light-duty trucks where API SP, SN Plus, ILSAC GF-6 and / or API SN, API SM, API SL quality oils are specified. Passenger cars and light-duty vehicles running on gasoline and ethanol-containing fuels up to E85. Suitable for modern turbo-charged direct injection gasoline engines where LSPI protection is required. ILSAC GF-6B is not backwards compatible with older engines.

### FEATURES & BENEFITS:

- Excellent engine cleanliness
- Engine protection under a wide variety of operating conditions
- Optimum power & performance under most severe driving conditions
- Fully compatible with all emission control devices and all gasoline grades
- Helps reduce engine wear and corrosion

### API LICENSE:

- SAE 5W30



### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-16	0W-20	0W-30	5W-20	5W-30	10W-30	5W-40	10W-40	15W-40	20W-50
<b>API</b>	SN PLUS (RC)/ SP (RC)	SN PLUS (RC)/ SP (RC)	SN PLUS (RC)/ SP (RC)	SN PLUS (RC)/ SP (RC)	SN PLUS (RC)/ SP (RC)	SN PLUS (RC)/ SP (RC)	SN PLUS/ SP	SN PLUS/ SP	SN PLUS / SP	SN PLUS / SP
<b>ILSAC</b>	GF-6B	GF-5	GF-5	GF-5	GF-5	GF-5	-	-	-	-
<b>GM</b>	-	DEXOS1	-	DEXOS1	DEXOS1	-	-	-	-	-
<b>CHRYSLER</b>	-	MS6094M	-	MS6094M	MS6094M	MS6094M	-	-	-	-
<b>FORD</b>	-	947A	-	945A	946A	-	-	-	-	-

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY NANO XP (Typical Specification)									
			0W-16	0W-20	0W-30	5W-20	5W-30	5W-40	10W-30	10W-40	15W-40	20W-50
KV @ 104°F /40°C	D7042	cSt	37.4	43.5	64	44.3	57.65	89.1	63.5	100.5	107.2	175.6
KV @ 212°F /100°C	D7042	cSt	7.2	8.3	11.5	8.3	10.3	14.8	10.3	14.8	14.9	19.5
Viscosity Index	D2270	-	160	170	177	166	170	175	151	154	145	128
SP. Gravity @15°C	D4052	g/cm <sup>3</sup>	0.840	0.840	0.843	0.846	0.845	0.844	0.875	0.870	0.885	0.89
Flash Point (min)	D92	°C	222	222	230	226	226	224	228	228	230	236
Pour Point (max)	D97	°C	-42	-42	-42	-42	-42	-42	-39	-36	-33	-24
TBN	D2896	Mg KOH/g	8	8	8	8	8	8	8	8	8	8
CCS	D5293	m.Pa.S	<6200 (-35°C)	<6200 (-35°C)	<6200 (-35°C)	<6600 (-30°C)	<6600 (-30°C)	<7000 (-25°C)	<7000 (-25°C)	<7000 (-25°C)	<7000 (-20°C)	<9500 (-15°C)

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.