



## VELOCITY GX9 20W-50 SEMI SYNTHETIC

### PRODUCT DESCRIPTION:

Velocity GX9 semi synthetic motor oil is formulated using the unique additives technology that allows the product to provide higher levels of cleansing and protection. It is a multigrade lubricant which meets the most difficult conditions of use (motorway, heavy urban traffic, etc.) during all seasons.

### APPLICATION:

Velocity GX9 is intended for use in modern highly accelerated gasoline and diesel engines of passenger cars, minibuses and light trucks which require API SL/CF performance level.

### FEATURES & BENEFITS:

- Superior wear and corrosion protection
- Protects against start-up wear in cold conditions through excellent low-temperature fluidity
- Maintains power and economy by minimizing wear
- Superior viscosity retention
- Oxidation resistant
- Engine Cleanliness and low combustion residue

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	20W-50
API	SL/CF
ACEA	A3/B3
RENAULT	RN 0700/0710
VW	501.01 / 505

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY GX9
<b>SAE Grades</b>			<b>20W-50</b>
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	19.5
Viscosity Index (min)	D2270	-	120
SP. Gravity @15°C/ 60°F	D4052	g/cm <sup>3</sup>	TBR
Flash Point (min)	D92	°C	220
Pour Point (max)	D97	°C	-24
TBN	D2896	mg KOH/g	8
CCS	D5293	m.Pa.S	<9500 (-15°C)

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.