



## E-COOL

### ETHYLENE GLYCOL BASED COOLANT FOR EVs

#### PRODUCT DESCRIPTION:

E-Coolant fluid with excellent heat removal capacity and resistance to oxidation at high temperatures. Especially suitable for indirect cooling of electric vehicle components such as batteries, electric motors or inverters that require good temperature control to optimize performance. EV Coolant is an aqueous mixture of Ethylene glycol and inhibitors.

#### FEATURES & BENEFITS:

- Compatible with the metals and alloys present in cooling circuits: aluminium, copper, cast metals, brass, and the most modern alloys.
- Compatible with joints, seals, and paints.
- Its high thermal resistance enables excellent engine cooling without the fluid boiling, preventing cavitation.
- Through its composition it is also environmentally friendly, as it does not contain nitrates, amines, or phosphates (NAP free).
- Product suitable for direct consumption as it contains treated water that avoids the formation of calcareous deposits and corrosion.
- Specifically designed for electric vehicles, it can also be used in those vehicles that require a quality level of MAN 324 types SNF and NF, as well as VW TL 774F and 774C, as long as it is not mixed with other products.

#### PERFORMANCE LEVELS: Meets or Exceeds:

- ASTM D 3306
- UNE 26-361-88
- BS 6580:2010
- SAE J 1034 and J 814
- MAN 324 type Si-OAT
- CUMMINS CES 14603
- Volkswagen VW TL 774 G (G12++)
- MB 326.5

#### TYPICAL PROPERTIES:

PARAMETERS	ASIM	UNIT	E-COOL
Density at 15°C	ASTM D5931	g/cm <sup>3</sup>	1.065
Freezing point	ASTM D1177	°C	-37
pH at 20°C	ASTM D1287	-	8.5

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point.

#### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

#### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

#### STORAGE:

We recommend storing all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.