



eFRICTION EV GREASE

PRODUCT DESCRIPTION:

eFriction is a long-lasting synthetic grease recommended for lubricating bearings, electric motors, and other electric vehicle components, with specially developed lubricating and conductivity properties to exceed the latest electric vehicle grease requirements. Achieve excellent protection and optimum performance.

APPLICATION:

It is recommended for high-speed electrical motor bearing lubrication in both wet and dry e-motor design battery electric vehicles. Synthetic grease uses our novel thickener technology to exceed the latest electric vehicle grease requirements.

FEATURES & BENEFITS:

- Grease is recommended for lubricating electric vehicle motor bearings.
- Suitable for lifetime lubrication.
- Valid for all weather conditions, and can operate from -50°C to 150°C.
- Its synthetic base provides excellent low-temperature pumpability, very low starting and running torque, and low pour point, resulting in excellent cold performance.

TYPICAL PROPERTIES:

PARAMETERS	ASIM	UNIT	eFRICTION
Colour	Visual		YELLOWISH
Consistency	NLGI		2/3
Thickener type	Complex lithium soap		Complex lithium soap
Base oil, viscosity at 40°C	ASTM D445	mm ² /s	85
Worked penetration at 60 strokes	ASTM D217	1/10 mm	260
Dropping point	METTLER FP-83HT	°C	280
Flow pressure at -50°C	DIN 51805	mbar	1150
Oxidation stability 100 h	ASTM D942	psi	3
4-ball Wear Scar (1 min/80 Kg)	ASTM 2266	ø,mm	0.45
Weld point	ASTM 2596	Kg	270
FAG FE9	ASTM D3527	h	>100
Life Performance at 160°C	ASTM D3527	h	140

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.