



MATERIAL SAFETY DATA SHEET

SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1Product identifier

Product Name:	LUBREX VELOCITY CNG PLUS 10W-30
Product Code:	918699
SDS No.:	L918699
Product Type:	Liquid

1.2Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance / Mixture:	ENGINE OIL
	For specific application advice see appropriate Technical Data Sheet
	or consult our company representative.

1.3Details of the Supplier of the Safety Data Sheet

Supplier:	Lubrex FZC, P.O 42438, Hamriyah Free Zone, Sharjah
	United Arab Emirates
Supplier Phone & Email Address:	Phone: +971 6 526 1200 Email: info@lubrex.net
Date of Issue	01-Jan-2023
Date of Revision	01-Jan-2024
Prepared by:	Lubrex FZC

1.4Emergency Telephone Number

Emergency Telephone Number:	United Arab Emirates, Government of Sharjah, Hamriyah Free Zone
	Authority, SAFETY PH NO. +971 6 526 1666 (24x7)
	EMERGENCY PH NO. +971 6 526 2111 (24x7)





SECTION 2: Hazard Identification

2.1Classification of the Substance / Mixture

Classification according to Directive	The product is not classified as dangerous according to Directive
1999/45/EC [DPD]	1999/45/EC and its amendments.
	See sections 11 and 12 for more detailed information on health
	effects and symptoms and environmental hazards.

2.2Label Elements

Signal Word:	No signal word.
Hazard Statements:	No known significant effects or critical hazards.
Precautionary Statements:	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Supplemental Label Elements:	Not applicable.
Special Packaging Requirements:	
Containers to be fitted	Not applicable.
with child-resistant	
fastenings	
Tactile Warning of Danger:	Not applicable.

2.3 Other Hazards

Defatting to the skin.
USED ENGINE OILS
Used oil may contain hazardous components, which have the
potential to cause skin cancer.
See Toxicological Information, section 11 of this Safety Data Sheet.





SECTION 3: Composition/Information on Ingredients

Substance / Mixture:

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%).

This product does not contain any hazardous ingredients at or above regulated thresholds.

SECTION 4: First Aid Measures

4.1Description of First Aid Measures

Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Eye Contact:	Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin Contact:	
	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Ingestion:	
	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if Symptoms occur.
Inhalation:	
	If inhaled, remove to fresh air. Get medical attention if symptoms appear. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Protection of First Aiders:	





No action shall be taken involving any personal risk or without suitable training.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3Indication of Immediate Medical Attention and Special Treatment Needed

Notes to Physician:	See Section 11 for more detailed information on health effects and
	symptoms.

SECTION 5: Fire Fighting Measures

5.1Extinguishing Media

Suitable Extinguishing Media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher
	or spray.

Unsuitable Extinguishing Media Do not use water jet.

5.2 Special Hazards Arising from Substance / Mixture

Hazards from the Substance or Mixture	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous Combustion Products	Combustion products may include the following: Carbon Oxides (CO, CO2) (carbon monoxide, carbon dioxide)

5.3Advice for Fire Fighters





Special precautions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

6.2 Environmental Precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and Material for Containment and Cleaning Up

Small SpillStop leak if without risk. Move containers from spill area. Absorbwith an inert material and place in an appropriate waste disposal



container. Dispose of via a licensed waste disposal contractor.

Large Spill Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, watercourses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4Reference to Other Sections

See Section 1 for emergency contact information.See Section 5 for firefighting measures.See Section 8 for information on appropriate personal protective equipment.See Section 12 for environmental precautions.See Section 13 for additional waste treatment information.

SECTION 7: Handling and Storage


7.1 Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for Safe Storage, Including Any Incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section





7.3Specific and End Use(s) Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure Controls / Personal Protection

8.1Control Parameters

Occupational Exposure Limits	No exposure limit value known measures.	
	Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.	
Recommended Monitoring Procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to	



national guidance documents for methods for the determination of hazardous substances will also be required.

exposure. In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory

Derived No Effect Level No DNELs/DMELs available

Predicted No Effect Concentration No PNECs available.

8.2 Exposure Controls

Appropriate Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organization for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.	
Individual protection measures	compatible.	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.	
Respiratory Measures	Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control	





protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Safety glasses with side shades

Eye / Self Protection

Skin Protection Hand Protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures). Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile Gloves

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained. If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes must be determined and rigorously followed.



Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks.

For Example:

• Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

• Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and Body: Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Respiratory protection: EN529 Gloves: EN420, EN374 Eye protection: EN166

Environmental Exposure Controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.





SECTION 9: Physical and Chemical Properties

9.1Information on Basic Physical and Chemical Properties

Appearance	
Physical State	Liquid
Color	Light Amber
Odour	Typical Petroleum
Odour threshold	Not Available
рН	Not Available
Melting point/freezing point	Not Available
Initial boiling point and boiling range	Not Available
Pour point	-36°C
Flash point	>180°C
Evaporation rate	Not Available
Flammability (solid, gas)	Not Available
Upper/lower flammability or	Not Available
explosive limits	
Vapor pressure	Not Available
Vapor density	Not Available
Relative density	Not Available
SP. Gravity @15°C/ 60°F	0.845 – 0.895 g/cm3
Solubility	Insoluble in water.
Partition coefficient:	Not Available
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
Viscosity	Kinematic Viscosity 11.52 cSt @ 212°F /100°C
Explosive properties	Not Available
Oxidizing properties	Not Available





9.20ther Information

No Additional Information

SECTION 10: Stability and Reactivity

10.1Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

10.2Chemical Stability

This product is stable.

10.3Possibility of Hazardous Reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

10.4Conditions to Avoid

Avoid all possible sources of ignition (spark or flame).

10.5Incompatible Materials

Reactive or incompatible with Oxidizing Materials





10.6Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

11.2Information on Toxicological Effects

Acute Toxicity Estimates	Route	ATE Value
Petroleum derived calcium salt	Oral	> 5000mg/kg
61789-86-4	Dermal	> 4000 mg/kg
	Inhalation (dusts and mists)	418.6 mg/l
Information on the likely routes of exposure	Routes of entry anticipated: Derm	al, Inhalation.
Potential Acute Health Effects		
Inhalation	Exposure to decomposition prod Serious effects may be delayed fo	ducts may cause a health hazard. llowing exposure.
Ingestion	No known significant effects or cr	itical hazards.
Skin Contact	Defatting to the skin. May cause skin dryness and irritation.	
Eye Contact	No known significant effects or cr	itical hazards.
Symptoms related to the physical,		
chemical and toxicological		
characteristics		
	No specific data	
Inhalation		
	No specific data	
Ingestion		

MSDS: LUBREX VELOCITY CNG PLUS 10W-30



Skin Contact Eye Contact	Adverse symptoms may include irritation, dryness, cracking No specific data
Delayed and immediate effects and also chronic effects from short and long term exposure Inhalation/Ingestion Skin Contact	Over exposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion of large quantities may cause nausea and diarrhea. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Potential Chronic Health Effects	Potential risk of transient stinging or redness if accidental eye contact occurs.
General	Used Oils : Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components, which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Carcinogenicity	No know significant effects or critical hazards. No know significant effects or critical hazards.
Mutagenicity Developmental Effects	No know significant effects or critical hazards.
Fertility Effects	No know significant effects or critical hazards.

SECTION 12: Ecological Information





12.1Toxicity

Environmental Hazard

Not classified as dangerous.

12.2Persistence and Degradability

Partially biodegradable.

12.3Bio Accumulative Potential

This product is not expected to bio accumulate through food chains in the environment.

12.4Mobility in Soil

Soil / Water partition coefficient	Not available	
(KOC)		
	Spillages may penetrate the se	oil causing ground water
Mobility	contamination	

12.5Result of PBT and vPVB Assessment

PBT	Not applicable

vPVB Not applicable

12.60ther Adverse Effects

Other ecological information	Spills may form a film on water surfaces causing physical damage	
	organisms. Oxygen transfer could also be impaired.	

SECTION 13: Disposal Considerations





13.1Waste Treatment Methods

Methods of Disposal	Where possible, arrange for product to be recycled. Dispose of via an authorized person/ licensed waste disposal contractor in accordance with local regulations.	
	Waste Code	Waste Designation
	13 02 08* Other engine, gear, and lubricating oils	
	However, deviation from the intended use and/or the presence of	
	an potential contaminants may require an alternative waste	
	disposal code to be assigned by the end user.	
Packing		
Methods of Disposal		uct to be recycled. Dispose of via an e disposal contractor in accordance
Special Precautions	This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

SECTION 14: Transport Information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN Number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN Proper Shipping Name	-	-	-	-
14.3 Transport Hazard Class	-	-	-	-
14.4 Packing Group	-	-	-	-
14.5 Environmental Hazards	NO	No	No	No
Additional Information	-	-	-	-
14.6 Special Precautions for User	Not available			

MSDS: LUBREX VELOCITY CNG PLUS 10W-30





SECTION 15: Regulatory Information

15.1Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization	None of the components are listed
Substances of very high concern Annex XVII - Restrictions on the manufacturer, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
Other Regulations REACH Status	The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.
United States Inventory (TSCA 8b) Australia Inventory (AICS) Canada Inventory China Inventory (IECSC) Japan Inventory (ENCS) Korea Inventory (KECI) Philippines Inventory (PICCS)	All components are listed or exempted. At least one component is not listed. At least one component is not listed.

15.2Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other Information

Abbreviations and ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland

MSDS: LUBREX VELOCITY CNG PLUS 10W-30





Acronyms	Waterway									
Actoriginis	ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road									
	ATE = Acute Toxicity Estimate									
	BCF = Bio Concentration Factor									
	CAS = Chemical Abstracts Service									
	CLP = Classification, Labeling and Packaging Regulation [Regulation (EC) No. 1272/2008]									
	CSA = Chemical Safety Assessment									
	CSR = Chemical Safety Report									
	DMEL = Derived Minimal Effect Level									
	DNEL = Derived No Effect Level									
	DPD = Dangerous Preparations Directive [1999/45/EC]									
	DSD = Dangerous Substances Directive [67/548/EEC]									
	EINECS = European Inventory of Existing Commercial chemical Substances									
	ES = Exposure Scenario									
	EUH statement = CLP-specific Hazard statement									
	EWC = European Waste Catalogue									
	GHS = Globally Harmonized System of Classification and Labeling of Chemicals									
	IATA = International Air Transport Association									
	IBC = Intermediate Bulk Container									
	IMDG = International Maritime Dangerous Goods									
	LogPow = logarithm of the octanol/water partition coefficient									
	MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified									
	by the Protocol of 1978. ("Marpol" = marine pollution)									
	OECD = Organization for Economic Co-operation and Development									
	PBT = Persistent, Bio Accumulative and Toxic									
	PNEC = Predicted No Effect Concentration									
	RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail									
	RRN = REACH Registration Number									
	SADT = Self-Accelerating Decomposition Temperature									
	SVHC = Substances of Very High Concern									
	STOT-RE = Specific Target Organ Toxicity - Repeated Exposure									
	STOT-SE = Specific Target Organ Toxicity - Single Exposure									
	TWA = Time weighted average									
	UN = United Nations									
	UVCB = Complex hydrocarbon substance									
	VOC = Volatile Organic Compound									
	vPvB = Very Persistent and Very Bio Accumulative									
Full tout of abbroutated U		11 204								
Full text of abbreviated H		H 304	May be fatal if swallowed and							
statements			enters airways. May cause long lasting harmful effects to aquatic life.							
		H 413								
Full text of classifications [CLP/GHS]										
		Aguatia Churchia 4 11410	·							
		Aquatic Chronic 4, H413	LONG-TERM AQUATIC HAZARD							
		Asp. Tox. 1, H304	- Category 4 ASPIRATION HAZARD -							





Category 1

Full text of abbreviated R Phrases	R53-	May	cause	long-term	adverse	effects	in	the	aquatic
	environment.								
Full text of classifications [DSD/DPD]									
	Not A	pplica	ble						
History									
Date of Issue	01/01	01/01/2023							
Date of Revision	01/01/2024								
Prepared by	Lubre	x FZC							

Notice to Reader:

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet. The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from Lubrex FZC. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Lubrex FZC shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the Lubrex FZC to ensure that this document is the most current available. Alteration of this document is strictly prohibited.