



RACE 4T NANO XP FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Race 4T Nano XP is an advanced engine oil designed to fulfill the rigorous requirements of motorcycle engines. It is specifically tailored for on-road, high-performance 4-cycle sport bikes but is also suitable for various other on and off-road 4-cycle motorcycles. Engineered to provide exceptional protection, it excels in 4-cycle, V-Twin engines, particularly those that are air-cooled and operate at higher temperatures compared to other engine types. Race 4T Nano XP delivers outstanding performance in both integrated engine/transmission lubrication systems and in systems where the engine and transmission lubrication are separate.

APPLICATION:

Recommended for all 4-Stroke motorcycles including cruisers and off-road motorcycles.

FEATURES & BENEFITS:

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

PERFORMANCE LEVELS: Meets or Exceeds:

- API SN
- JASO MA2

API LICENSE:



TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RACE 4T NANO XP
Grade			20W-50
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	20.5
Viscosity Index (min)	D2270	-	120
Density@15°C/ 60°F	D4052	g/cm ³	TBR
Flash Point (min)	D92	°C	220
Pour Point (max)	D97	°C	-24

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.