



DRIVEMAX HD

PRODUCT DESCRIPTION:

Drivemax HD is a high-performance synthetic transmission fluid engineered to meet the rigorous demands of modern heavy-duty automatic transmissions. Formulated with advanced synthetic base oils and cutting-edge additives, it ensures exceptional gear shifting and efficient power transfer. The fluid offers excellent resistance to thermal degradation at elevated temperatures while maintaining reliable performance in sub-zero conditions. Its robust formulation supports significantly extended drain intervals.

APPLICATION:

Drivemax HD is specially formulated for extended drain intervals in heavy-duty transmission systems. It is recommended for use in modern, high-performance trucks, buses, utility vehicles, haulers, vans, and other equipment that require a transmission fluid meeting Allison TES 295 performance standards.

FEATURES & BENEFITS:

- Extended drain interval
- Exceptional oxidation resistance
- Smooth shifts and lock-ups
- Excellent low temperature fluidity
- Wide range elastomer compatibility
- Excellent corrosion resistance

PERFORMANCE LEVELS: Meets or Exceeds:

- Allison TES-295
- Allison TES-468
- MB-Approval 236.91
- VOITH TURBO DIWA Service Bulletin 013 -Extended Drain
- VOITH TURBO DIWA Service Bulletin 118 - Extended Drain
- VOITH TURBO H55.6336.3x
- VOITH TURBO H55.6335.3x
- VOLVO 97341
- GM DEXRON IIIH
- ZF TE-ML 04D/14A/14B/14C/16L/16M/16S/20C/25C
- MAN 339 Typ V2/Z12/Z3
- CATERPILLAR AT-1

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	DRIVEMAX HD
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	7.3
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR
Viscosity Index (min)	ASTM D-2270	-	181
Density@15°C/ 60°F	ASTM D-4052	g/cm3	TBR
Flash Point (min)	ASTM D-92	°C	218
Pour Point (max)	ASTM D-97	°C	-45

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.