OCTANE BOOSTER



Octane Booster is a high-performance fuel additive formulated using advanced octane-boosting technology. It is designed to increase the Research Octane Number (RON) of petrol by up to 6 points. *Depending on fuel quality and treatment rate.

The advanced formulation helps improve fuel knock resistance, promotes efficient combustion and supports improved engine response. Regular use also helps maintain fuel-system cleanliness and reduce deposit formation.

APPLICATION:
Suitable for petrol/gasoline engines.

DIRECTION FOR USE:
Add directly into fuel tank, preferably before refuelling to ensure through mixing.

CONSUMPTION:
330 ml treats up to 70 liters of fuel.

EFFECT:
Active during normal engine operation.

TECHNICAL DATA:

Physical state	:	Liquid
Colour	:	Reddish brown
Odour	:	Characteristic
Flashpoint	:	24 °C
Density at 59 °F	:	0.87 - 0.89 g/cm^3
Water resistant		

Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.

HEALTH & SAFETY, ENVIRONMENT:
Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:
This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:
Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:
We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005
All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.